



Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. A variety of flow rates are available.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Seal kit - Cartridge	Buna: 990008007
Seal kit - Cartridge	EPDM: 990008014
Seal kit - Cartridge	Polyurethane: 990008002
Seal kit - Cartridge	Viton: 990008006

**CONFIGURATION OPTIONS**

**Model Code Example: FXAAXAN**

CONTROL	(X) FLOW RATE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>A</b> 15 in <sup>3</sup> /min. (250 cc/min.) <b>B</b> 20 in <sup>3</sup> /min. (330 cc/min.) <b>D</b> 40 in <sup>3</sup> /min. (660 cc/min.) <b>F</b> 60 in <sup>3</sup> /min. (1 L/min.) <b>H</b> 80 in <sup>3</sup> /min. (1.3 L/min.) <b>J</b> 100 in <sup>3</sup> /min. (1.6 L/min.) <b>L</b> 120 in <sup>3</sup> /min. (2.0 L/min.)	<b>N</b> Buna-N <b>E</b> EPDM <b>V</b> Viton	Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel