



Two-position, 3-way directional cartridges are 6-port (port 5 is not used) directional valves that can be configured with up to 5 different spool configurations. The supply port is port 3 and all ports will accept 5000 psi (350 bar). Capacity for these pilot-to-shift valves is dependent on the spool type specified.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Minimum Pilot Pressure Required to Shift Valve	10 bar
Pilot Pressure Required for Full Shift at Rated Flow	20 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,82 cc
Seal kit - Cartridge	Buna: 990052007
Seal kit - Cartridge	Viton: 990052006

**CONFIGURATION OPTIONS**

Model Code Example: **DDGXCN**

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>C</b> Closed Crossover O Open Crossover R Restricted Crossover Y All Ports Blocked Z All Ports Open	<b>N</b> Buna-N V Viton	Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel