



This valve is a 3-way, 3-position proportional directional valve. Port 3 is closed in the center position and port 2 and port 4 are drained to port 1. Pilot pressure at port 1 creates a metering orifice between ports 3 and 4 that is proportional to the pressure at 1. Piloting 6 opens 3 to 2. The force balance of the flow forces, spring and pilot pressure results in a degree of partial self-compensation as the load pressure changes.

Load sense is available at port 5 when the spool is shifted to either port 2 or 4.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Minimum Pilot Pressure Required to Shift Valve	3,5 bar
Pilot Pressure Required for Full Shift at Rated Flow	20 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.
Pilot Volume Displacement	0,66 cc
Hysteresis	± 2 %
Seal kit - Cartridge	Buna: 990052007
Seal kit - Cartridge	Viton: 990052006

CONFIGURATION OPTIONS

Model Code Example: FTCKXCN

CONTROL	(X)	SPOOL CONFIGURATION	(C)	SEAL MATERIAL	(N)
X Not Adjustable		C Normally Closed		N Buna-N	
				V Viton	